14 oz. INDOOR VINYL COLOR CHART



01-01-2024



Color output may not be exact as on this document due to variations in monitors and printers. Color approval must be based on specific colors (vinyl samples, ink samples, digital print samples, etc.) rather than their visual representation in this document. The designs and layouts in this document are the property of Sportsfield Specialties and may not be reproduced without permission and/or written consent.

PRODUCT SPECIFICATIONS

	Value	Test Method
Weight	14 oz. / yd²	ASTM D3776
Construction	9 x 9, 1000 x 1000 Denier	N/A
Grab Tensile (lb / in)	Warp 365 / Fill 348	ASTM D5034
Tongue Tear (lb / in)	Warp 92 / Fill 83	ASTM D2261
Adhesion	28 lbs / 2"	ASTM D751
Cold Crack	-4° F	ASTM D2136
Treatments	Anti-Mildew, UV	N/A
Flame Retardant	Pass	ASTM E84 (Class A), California State (CSFM), NFPA-701

RECOMMENDED USES

Indoor Wall Pads Indoor Column Pads Indoor I-Beam Pads

Dasher Board Pads Fire Rated Stage Mats

01-01-2024



Color output may not be exact as on this document due to variations in monitors and printers. Color approval must be based on specific colors (vinyl samples, ink samples, digital print samples, etc.) rather than their visual representation in this document. The designs and layouts in this document are the property of Sportsfield Specialties and may not be reproduced without permission and/or written consent.